ALTV248ULHI, ALTV248ULCBHI UL Listed AC Isolated CCTV Power Supply

Rev. DSALTV248ULHI - A04G

Overview

- These Altronix Isolated CCTV Power Supplies provide 24VAC distributed via eight (8) isolated fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV248ULHI

- Eight (8) isolated fused protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV248ULHI3

ALTV248ULHI w/3-wire Line Cord.

ALTV248ULCBHI

- Eight (8) isolated Class 2 Rated PTC protected outputs.
- Outputs are rated @ 2.5 amp.

ALTV248ULCBHI3

ALTV248ULCBHI w/3-wire Line Cord.

Specifications

- Input 115VAC, 50/60 Hz, 3 amp.
- 24VAC @ 12.5 amp (300VA) supply current.
- Primary fuse rated @ 5 amp/250V.
- Eight (8) 1.56 amp isolated outputs.
- Illuminated power disconnect circuit breaker with manual reset.
- Spare fuses provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.
- Product weight:
  - ALTV248ULHI: 12.7 lbs.
  - ALTV248ULCBHI: 12.7 lbs.
- Shipping weight:
  - ALTV248ULHI: 13.4 lbs.
  - ALTV248ULCBHI: 13.4 lbs.

Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

European Conformity

Enclosure Dimensions

13”H x 13.5”W x 3.25”D